

# Steelforce Pro 470 SLS

## Dual step, sit-stand height electrically adjustable

|                       |                       |
|-----------------------|-----------------------|
| Height (mm)           | min. 615 / max. 1275  |
| Stroke (mm)           | 660                   |
| Speed (mm/s)          | 39                    |
| Width (mm)            | min. 1100 / max. 1700 |
| Depth of feet (mm)    | 750                   |
| Column size (mm)      | 70 x 70               |
| Dynamic capacity (kg) | 80                    |
| Noise dB(A)           | <55                   |
| Power                 | V 220 - 230           |
| Plug type             | Replaceable           |
| Weight (kg)           | 30                    |

Legs, feet, top supports & crossbars made of powder coated steel.  
Softstart & -stop function.  
Spindle lifting system & low energy consumption.

## Surface color

|        |   |               |                  |
|--------|---|---------------|------------------|
| Silver | ● | Purchase code | SLS30000000383EU |
| White  | ○ |               | SLS30000000329EU |

## Packing dimension single unit

960 x 285 x 185 (LxWxH - mm)

## Packing dimension pallet (20 frames)

1140 x 1130 x 1060 (LxWxH - mm)

## Accessories

Please see the accessories section to personalise your height adjustable frame.



Tested according to Japan domestic standard by TÜV Rheinland.  
Tested according to IEC 60335-1 by Intertek.

